

Hand-dug Caisson Worker Skilled Trade Test Mock Written Test Paper

此文件關於手挖沉箱工工藝測試考題。如有需要索取此文件的中文版本，請致電 2100

9232 與工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.

Enquiries

Enquiries on this Material may be made to the Trade Test Centre at:

95, Yue Kwong Road
Aberdeen
Hong Kong

Tel: (852) 2100 9232
Fax: (852) 2100 9249
Email: enquiry@cic.hk
Website: www.cic.hk

1. When digging a caisson under favourable geological conditions, the depth of each section is in general:
 - (a) Under 1 m
 - (b) 1½ m
 - (c) 2 m
 - (d) 2½ m

2. Which of the following will generally be used in calibrating the position and verticality of formwork?
 - (a) Tower crane
 - (b) Tighten with screws
 - (c) Rope
 - (d) Plumb bob

3. When conducting hand-dug caisson work, there should be no:
 - (a) Disaster first-aid equipment nearby
 - (b) Safety officer inspecting nearby
 - (c) Activity of heavy machinery nearby
 - (d) Site supervisor monitoring nearby

4. The cradle supporting the electric winch (電絞轆) should be:
 - (a) Metal gantry
 - (b) Heavy duty alloy steel frame
 - (c) Secured and inspected by a competent inspecting person
 - (d) Iron trestle with anti-rust paint

5. Electric winch (電絞轆) must be operated by:
 - (a) Persons having received safety enhancement training
 - (b) Persons aged 18 and having received training
 - (c) Persons who know the specifications of electrical installations
 - (d) Direct employees of the main contractor

6. Where should the gas testing personnel be when conducting gas testing?
- (a) Directly above the manhole
 - (b) Bottom of the caisson
 - (c) Safe location
 - (d) Mid-section of the caisson
7. Workers who suspect themselves of being affected by silicon dust should:
- (a) Stop working immediately and rest at home
 - (b) Reduce working hours and do more chest expansion exercise
 - (c) Enquire a thoracic doctor as soon as possible
 - (d) Buy drugs from a pharmacy to take
8. Miscellaneous articles in the formwork must be cleared away before placing concrete so as not to:
- (a) Save manpower
 - (b) Make the articles float
 - (c) Affect the strength of the concrete
 - (d) Affect the structural strength of the formwork
9. According to the statutory requirement, an electrical winch (電絞轆) for material hoisting should be inspected within a maximum interval of:
- (a) 9 months
 - (b) 3 months
 - (c) 6 months
 - (d) 12 months

10. When there is suspicion on the air safety level, workers in the caisson should:
- (a) Continue to work carefully
 - (b) Enhance the efficiency of the ventilation system immediately and continue to work
 - (c) Continue to work and immediately notify the person-in-charge to conduct gas testing
 - (d) Evacuate immediately
11. Apart from appointing a competent person for gas testing, the contractor must also conduct:
- (a) Cost assessment
 - (b) Traffic assessment
 - (c) Report on completion of work
 - (d) Noise assessment
12. The length of a stone jaw (石夾片) for “wedging (開尖)” is usually:
- (a) 250 mm
 - (b) 300 mm
 - (c) 350 mm
 - (d) 400 mm
13. Under normal circumstances, the largest internal diameter of a hand-dug caisson is:
- (a) 1 m
 - (b) 2 m
 - (c) 3 m
 - (d) 4 m

14. The minimum internal diameter of a caisson after lining (襯砌) is:
- (a) 400 mm
 - (b) 600 mm
 - (c) 800 mm
 - (d) 1000 mm
15. When lifting or lowering the sinking bucket (吊泥桶), attention must be paid whether:
- (a) The bucket is full and overflowing
 - (b) The safety lock of the switch of the bucket is locked
 - (c) The rim of the bucket is clean and hygienic
 - (d) The size of the bucket fits the moving worker
16. The length of a drill rod for rock cutting (介石) is usually:
- (a) 400 mm
 - (b) 500 mm
 - (c) 600 mm
 - (d) 700 mm
17. Entry to caissons that have completed digging or suspended from work must be:
- (a) Covered by 9 mm plywood
 - (b) Sealed off with cement mortar
 - (c) Securely concealed by a firm covering
 - (d) Partly concealed by cast iron panel for manhole

18. The definition of work at height means the distance between the work location and the ground is:
- (a) 1 m or above
 - (b) 2 m or above
 - (c) 3 m or above
 - (d) 4 m or above
19. According to the statutory requirement, the minimum thickness of planks laid on a working platforms is:
- (a) 20mm
 - (b) 25mm
 - (c) 30mm
 - (d) 35mm
20. According to the statutory requirement, appropriate guard rails must be installed on a working platform and the height should not be less than:
- (a) 800mm
 - (b) 900mm
 - (c) 1000mm
 - (d) 1100mm