



CONSTRUCTION
INDUSTRY COUNCIL
建造業議會

Construction Plant Mechanic Skilled Trade Test Mock Written Test Paper

此文件關於鋪瓦工 (瓷瓦) 工藝測試考題。如有需要索取此文件的中文版本，請致電 2100 9232 與工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.

Enquiries

Enquiries on this Material may be made to the Trade Test Centre at:

95, Yue Kwong Road
Aberdeen
Hong Kong

Tel: (852) 2100 9232
Fax: (852) 2100 9249
Email: enquiry@cic.hk
Website: www.cic.hk

1. This symbol denotes :
 - (a) uni-directional constant pump
 - (b) bi-directional variable pump
 - (c) revolving constant motor
 - (d) revolving variable motor

2. Which one of the following type of control valves is denoted by this symbol ?
 - (a) pressure release valve
 - (b) vacuum meter
 - (c) energy reservator
 - (d) throttle valve

3. The correct sequence of tightening screws of the cylinder head should be :
 - (a) from right to left
 - (b) from left to right
 - (c) toward the centre
 - (d) away from the centre

4. The opening the inlet valve early and closing it late can :
 - (a) reduce abrasion of valve
 - (b) reduce explosion of engine
 - (c) reduce air leakage of valve
 - (d) increase the capacity efficiency of cylinder

5. Which of the following internal combustion engine components is used to control timing of inlet and exhaust valve during the piston motion ?
 - (a) connecting rod
 - (b) fly wheel
 - (c) crank shaft
 - (d) cam axial

6. For a hydraulic excavator undercarriage, which of the following components surrounds the motion structure ?
- (a) shoe plate
 - (b) track link
 - (c) sprocket
 - (d) lower roller
7. According to the provisions of the Construction Sites (Safety) Regulation, all types of lifting appliances and lifting gear should be :
- (a) disposed regularly
 - (b) inspected regularly
 - (c) installed with an air conditioner
 - (d) inspected and examined regularly
8. When there is a continuous oil leakage from the carburetor of a petrol driven poke vibrator, it reveals that :
- (a) the condition is normal
 - (b) the delta has raised
 - (c) has not been switched off
 - (d) the carburetor screws have not been tightened up
9. Which of the following reasons that makes starting or igniting of the petrol driven poker vibrator ?
- (a) petroleum has been used up
 - (b) high-voltage cable has been earthened
 - (c) spark plug does not function
 - (d) all of the above

10. Which of the following tools is represented by this symbol ?
- (a) socket
 - (b) ring spanner
 - (c) combination spanner
 - (d) adjustable spanner
11. Which of the following equipment can be used to measure the outer diameter of piping ?
- (a) outside caliper
 - (b) caliper
 - (c) both (a) and (b)
 - (d) neither (a) nor (b)
12. In electric system, this symbol denotes :
- (a) fuse
 - (b) diode
 - (c) transformer
 - (d) relay
13. The unit of co-efficient of electric current resistance is :
- (a) M
 - (b) G
 - (c) V
 - (d) Ωm
14. Which of the following materials has the best conductivity ?
- (a) copper
 - (b) silver
 - (c) iron
 - (d) chromium

15. What type of welding is denotes by this diagram ?
- (a) flat
 - (b) vertical
 - (c) horizontal
 - (d) upper
16. Which of the following components is denotes by this diagram ?
- (a) Argon meter
 - (b) flash back arrestor
 - (c) wire feed
 - (d) oxy-acetylene guage
17. What will happen to welding seams when the electrode becomes damp during welding :
- (a) undercut
 - (b) porosity
 - (c) inclusion
 - (d) lead fire
18. Which of the following ways is **INCORRECT** in handling safety helmet ?
- (a) putting sticker or label on the helmet
 - (b) adding ear protector to the helmet
 - (c) drilling hole on the helmet
 - (d) using the mouth mask together with the helmet
19. According to the relevant regulation, any person entering the construction site should be at least :
- (a) 15 years old
 - (b) 16 years old
 - (c) 18 years old
 - (d) 20 years old

20. Before a bulldozer is repaired , it should be placed on :
- (a) inclined road
 - (b) level ground
 - (c) slope of a hill
 - (d) uneven ground