



CONSTRUCTION
INDUSTRY COUNCIL
建造業議會

Floor Layer (PVC Flooring) Trade Test Mock Written Test Paper

此文件關於鋪地板工（塑料地板）工藝測試考題有需要索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.

Enquiries

Enquiries on this Material may be made to the Hong Kong Construction Industry Trade Testing Centre at:

95, Yue Kwong Road
Aberdeen
Hong Kong

Tel: (852) 2100 9000
Fax: (852) 2100 9090
Email: enquiry@cic.hk
Website: www.cic.hk

© 2020 Construction Industry Council.

1. Which glue is more suitable on skirts (the vertical risers) of a staircase?
 - A. All-purpose adhesive
 - B. Mixed glue
 - C. Aron Alpha instant glue
 - D. White glue

2. What is the most common method of laying PVC flooring?
 - A. Side by side
 - B. In cross pattern
 - C. In the pattern of 'I'
 - D. In the pattern of a square

3. If the welding machine is too hot or moves too slowly...
 - A. The vinyl sheet flooring will be burnt
 - B. The PVC flooring will fail to be laid
 - C. The PVC flooring will become loose
 - D. The PVC flooring will start to develop gaps

4. The connecting parts of the plastic stairnose should be cut at what angles to facilitate connection?
 - A. 45-degree angles
 - B. 30-degree angles
 - C. 60-degree angles
 - D. 90-degree angles

5. What is a more suitable material to repair an uneven floor slab?
 - A. White glue
 - B. Floor glue
 - C. Glass sealant
 - D. Mixtures

6. Besides mitring, what is another common way to connect at a visible joint ?
 - A. Splicing the joint
 - B. Connecting at 45-degree angles
 - C. Butterfly corner
 - D. Stacking the corners

7. If the vinyl sheet flooring is bent upwards against the wall as skirting, what is the usual height of the skirting in mm ?
 - A. 40mm
 - B. 60m
 - C. 80mm
 - D. 100mm

8. According to the Factories and Industrial Undertakings (Safety Management) Regulation, how often should safety policy be reviewed?
 - A. 1 year
 - B. 2 years
 - C. 3 years
 - D. 4 years

9. Which of the following is a danger one might encounter in a confined space?
 - A. Drowning of any person at work arising from an increase in the level of liquid
 - B. The loss of consciousness or asphyxiation of any person at work arising from the lack of oxygen
 - C. The intoxication of the person at work from poisonous air
 - D. All of the three options should be take into account

10. After laying the waterproof plastic sheet or bituminous sheet, why is there still water seepage?
- A. Sufficient overlapping of the materials
 - B. Insufficient overlapping of the materials
 - C. There are two layers of overlapping of the materials
 - D. The overlapping parts have been glued together
11. Which is a more suitable tool to connect the welding lines on the connecting parts of the vinyl sheet flooring?
- A. Electric heating machine
 - B. Flaming torch
 - C. Swing machine
 - D. Welding machine
12. Which is a more accurate tool to mark the connecting parts, whose underside is covered by the vinyl sheet flooring?
- A. Auxiliary Wire Gauge (The little mouse)
 - B. Measuring Tape
 - C. Cutting tools
 - D. Welding machine
13. How far from the ground would be considered as working-at-height?
- A. 4 metres or above
 - B. 3 metres or above
 - C. 2 metres or above
 - D. 1 metre of above
14. If there is a need to separate vinyl sheet flooring by colours, how should it be distinguished when preparing the materials?
- A. Scorched a mark on the surface of the vinyl sheet flooring
 - B. No attention is needed; rely on your memory
 - C. No attention is needed; lay the flooring in whatever way possible
 - D. Marking colour codes on the bottom of the vinyl sheet flooring

15. When the distribution board is on fire, what type of fire extinguisher should be used?
- A. Dry powder fire extinguisher
 - B. Water type fire extinguisher
 - C. Spray type fire extinguisher
 - D. Carbon dioxide fire extinguisher
16. After completing laying the flooring, there should not be any unnecessary job lines and?
- A. Water stains
 - B. Dust stains
 - C. Chalk stains
 - D. Glue stains
17. What should be used as the starting point in the most correct way to lay PVC flooring?
- A. Starting point of the job lines
 - B. Any point
 - C. Starting point of a wall corner
 - D. Starting point of a door jamb
18. What is the most appropriate width for vinyl sheet flooring for welding pits?
- A. 8 mm
 - B. 6 mm
 - C. 4 mm
 - D. 2 mm
19. After repairing the floor slab, how much time should be spared before glue can be applied?
- A. 15 to 30 minutes
 - B. 1 to 3 minutes
 - C. 5 to 10 minutes
 - D. 60 to 90 minutes

20. What should best be worn to protect your hearing while working in an area with high level of noises?

- A. Ear Protectors
- B. Safety goggles
- C. Face mask
- D. Non-slip gloves

End of Paper