



CONSTRUCTION
INDUSTRY COUNCIL
建造業議會

Bricklayer Skilled Trade Test Mock Written Test Paper

此文件關於砌磚大工工藝測試考題。如有需要索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.

Enquiries

Enquiries on this Material may be made to the Hong Kong Construction Industry Trade Testing Centre at:

95, Yue Kwong Road
Aberdeen
Hong Kong

Tel: (852) 2100 9000

Fax: (852) 2100 9090


Email: enquiry@cic.hk

Website: www.cic.hk

© 2018 Construction Industry Council.


1. The part " X " of the wall capping is called:

- (a) brick
- (b) soil
- (c) concrete
- (d) hard core




2. The part " Q " of brick laying is called :

- (a) half brick
- (b) header
- (c) single brick
- (d) arch brick



3. The length of the diagonal is:

- (a) 2.75 M
- (b) 2.5 M
- (c) 2.25 M
- (d) 1.75M



4. The dimensions of a common red brick are:

- (a) 225 x 112.5 x 75 mm
- (b) 205 x 112.5 x 55 mm
- (c) 225 x 102.5 x 75 mm
- (d) 225 x 112.5 x 55 mm

5. To lay a single 70 mm thick and 105 mm wide brick wall, the bond should be:
- (a) English bond
 - (b) Flemish bond
 - (c) Coping brick bond
 - (d) Common brick bond
6. The maximum tolerance of the verticality of a brick wall in 3 M height is:
- (a) 5mm
 - (b) 10mm
 - (c) 15 mm
 - (d) 20mm
7. The sand used for a brick work shall pass through a:
- (a) 1 mm sieve
 - (b) 5 mm sieve
 - (c) 10 mm sieve
 - (d) 15 mm sieve
8. The function of hanging a string at arris is to:
- (a) measure the thickness of mortar
 - (b) keep the bedding thickness regular
 - (c) use the line as a verticality guide
 - (d) measure the wall height
9. The time used for mixing the mortar by machine is approximately:
- (a) 1 minute
 - (b) 5 minutes
 - (c) 15 minutes
 - (d) 30 minutes

10. Before laying a brick wall over a door frame, which of the following materials should be needed?
- (a) layer brick
 - (b) piece of wood
 - (c) piece of steel bar
 - (d) precast lintel
11. To lay a turn angle brick wall at a corner, we may consider:
- (a) window bay
 - (b) fix lugs
 - (c) socket position
 - (d) tothing
12. The best timing to make good the arris brick joint is:
- (a) 2 days after brick laying
 - (b) same day as brick laying
 - (c) a day after brick laying
 - (d) 3 days after brick laying
13. The function of a gauge rule is :
- (a) cleaning brick surface
 - (b) maintain vertical joint
 - (c) brick joint pointing
 - (d) maintain regular bedding thickness
14. Which of the following materials will have a shiny reflective surface:
- (a) red brick
 - (b) sand brick
 - (c) glazed brick
 - (d) thermal brick

15. Which of the following materials will have another name as tile:
- (a) red brick
 - (b) sand brick
 - (c) hollow brick
 - (d) burnish brick
16. The fine aggregate used for brick laying is:
- (a) soil sand
 - (b) lime sand
 - (c) white powder sand
 - (d) cement sand
17. The purpose of wearing safety helmet is to:
- (a) resist rain and wind
 - (b) protect our head
 - (c) avoid caught a cold
 - (d) clarify the grade of workers
18. The minimum thickness of a plank used on a bamboo scaffolding is:
- (a) 20 mm
 - (b) 25mm
 - (c) 30 mm
 - (d) 35 mm
19. If a worker is hurt by a rust nail, he may get:
- (a) enteric fever
 - (b) a cold
 - (c) tetanus
 - (d) tuberculosis

20. The purpose of conducting "Tool Box Talk "is to:
- (a) according to an ordinance
 - (b) introduce safety design
 - (c) discuss works progress
 - (d) convey safety knowledge to workers