

Tiler (Tile)

Intermediate Trade Test

Study Material for Written Test

(Version : ITE-SM-EN-01)



此文件關於鋪瓦工（瓷瓦）中級工藝測試技術知識測試（筆試）內容參考資料。
如需索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or by any means without the written permission from the Construction Industry Council (CIC). Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions. The CIC will not assume any liability in relation to any loss or damage directly or indirectly resulted from unintended or/and unforeseeable use of this document.

This document is provided as reference for test preparation only. Under all circumstances all content in the official test papers, including but not limited to the terms and conditions therein, prevails.

The CIC reserves the right, at its sole and absolute discretion, to change, update or delete the contents in this document at any time without prior notice.

The CIC reserves all rights of final interpretation for any content in this document.

Enquiries

Enquiries on this material may be made to Hong Kong Construction Industry Trade Testing Centre at:

Address: 95 Yue Kwong Road, Aberdeen, Hong Kong

Tel: (852) 2100 9000


Fax: (852) 2100 9090

Email: hkcittc@cic.hk

Website: www.cic.hk

Tiler (Tile) Intermediate Trade Test Study Material for Written Test

This study material is a reference for candidate to prepare for attending written test in Intermediate Trade Test:

1. The symbol shown in the diagram represents level. 
2. Surface finishes work should be start at 7 days after completed the rendering coat.
3. The function of groove/drip line is to intercept the flow of rainwater.
4. Clip corner of ceramic tiles is commonly applied at external angles.
5. The mix proportion of cement and sand for cement mortar in paving floor tiles is 1:3.
6. Tile joint filler/pointing should take place at 1 day after tiling works complete.
7. In general, for ceramic tiles to be paved on walls in kitchen or bathroom, its end is located where it reaches the ceiling or soffit of beam.
8. The function of expansion joint on floor or external walls is to relieve the effect of thermal expansion and contraction.
9. Aligned work surfaces across different walls refer to working surfaces are aligned to become a straight line.
10. Tiles laid like shoe fitting floor mirror refer to tiles laid at chamfer between wall toe and floor.
11. During tiling, the correct way to apply tile grout (tile adhesive) is smearing the bottom/back surface of the tiles evenly.
12. Before tiling, two reference lines with intersection angle of 90o will be marked on the floor for setting out purpose.
13. For tiling ceramic tiles at clip corner, cutter (i.e. electric cutter) is used.
14. To level the tile adhesive during tiling, notched trowels should be use.
15. While working at height, in addition to the safety helmet, safety belt and independent lifeline should be properly used.

16. According to Construction Sites (Safety) Regulations, no person should enter a construction site unless he/she is wearing a suitable safety helmet.
17. After finishing works in everyday, tools and work site should be cleaned.
18. The proper attitude towards boss at work is to realize the job requirements, follow the instruction given by your supervisor and seek for advice if any queries.
19. In case of foreign object in the eye, clean water should be used to flush the foreign object out of the eye.
20. The best method of moving heavy object is utilizing machine as much as possible.

Precautions

This document is provided as reference for test preparation only. Under all circumstances all content in the official test papers, including but not limited to the terms and conditions therein, prevails. There are different versions of the test paper, content include but not limited to tools, materials, equipment, drawing, construction details or procedures and different simulated site environments. Candidates should refer to the official test documents during testing.

The CIC reserves the right, at its sole and absolute discretion, to change, update or delete the contents in this document at any time without prior notice.